

BE-EXP-1217E



The 1217E fixture withstands extreme temperatures, explosion and fire hazards, as well as flammable gases and vapours. This driverless LED fixture can withstand temperatures up to 85°C with CID1/CIID1 and CID2 classification ratings.

Ideal for high heat environments, petrochemical complexes, painting facilities, offshore platforms, oil and gas complexes, and more.



- · CID1 Group B, C, D
- · CIID1 Group E, F, G
- · CID2 Group A, B, C, D
- Temperature Rating of -40°C ~ +85°C
- · 6KV Surge Protection Built-In
- Various Mounting Options
- · Driverless Hazardous LED
- · Lifespan of 60,000 Hours















SPECIFICATIONS

Luminous Efficacy	100lm/W		
ССТ	3000K, 5000K (Standard)		
CRI	>Ra80		
Beam Angle	>110°		
Input Voltage	120V / 277V		
IP Rating	IP68		
Lifespan	60,000 Hours		
Entry Thread	Female NPT 3/4" - Straight Electrical Tube		
Operating Temp.	-40°C up to +85°C (120W) -40°C up to +65°C (150W)		
Warranty	65°C and Below - 5 Year Warranty 65°-85°C - 2 Year Warranty		
Certifications	UL, cUL		
Classifications	CID1 Group B, C, D / CIID1 Group E, F, G		

CID2 Group A, B, C, D


LUMENS	WATTAGE	EQUIVALENT
15,000lm	150W	600W
12,000lm	120W	400W




BE-EXP-1217E

Mounting Options


25° WALL MOUNT (WHT)




90° WALL MOUNT (WHT)




25° HANGING MOUNT (WHT)



90° HANGING MOUNT (WHT)






Fixture Ordering Matrix

Product Name	Wattage	Input Voltage	сст	Classification	Options
BE-EXP-1217E	120W 150W	120V 277V	3000K 5000K (Standard)	CID1 / CIID1 CID2	WHT Adjustable Wall/Hanging Mount PM Pendant Mount with Coupling SC Safety Cable SGS Surge Suppressor

Example: BE-EXP-1217E-120W-120V-5000K-CID1-WHT-SC-SGS

Dimensions & Shipping Information





Fixture Weight: 24 lbs

Weight w/Bracket: 27 lbs



Canadian Purchase Orders ship from our Canadian warehouse located at:

1178 Bighorn Ave Pincher Creek, AB T0K 1W0 Canada



USA

USA Purchase Orders ship from our US warehouse located at:

910 S. Industrial Park Road Shelby, MT 59474 USA



SUPPORT:

We sell exclusively through distributors. If you are a manufacturing plant, we are happy to work with you and your supplier of choice.

Our lead time on standard items is 5-7 business days.

For IES Files, lighting layouts or further questions, please contact one of our sales representatives.