



Classification	Standard
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	73 W
Reported Light Output	10555 lm
Reported CCT	5000 K
Reported CRI (Ra)	73
Product ID	S-9XU6MI
DLC Family Code	YYYYFHF
Listing Status	Listed
Date Qualified	2022-06-13

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-9XU6MI
Manufacturer	Back To Earth Energy Inc
Brand	LED IN ACTION
Model Number	BE-CHB-70W-D120-B-5000K
Parent	No
Classification	Standard
DLC Family Code	YYYYFHF
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	10555 lm
Reported Efficacy (AC)	144.55 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	73
Reported R9	-29
Reported IES Rf	74
Reported IES Rg	94
Reported IES Rcs,h1	-18
Reported Default Light Output	10555 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	73 W
Reported Total Harmonic Distortion	8.4 %
Reported Power Factor	0.905
Reported Default Input Wattage	73 W
Voltage Range	100-277 V

VERSION HISTORY VIEW DETAILS

2022-12-07	Listed	5.1	Standard
2022-12-06	Listed	5.1	Standard
2022-12-05	Listed	5.1	Standard
2022-11-10	Listed	5.1	Standard
2022-06-13	Listed	5.1	Standard