

# DesignLights Consortium



Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	449.2 W
Reported Light Output	71956 lm
Reported CCT	5000 K
Reported CRI (Ra)	74
Product ID	PEU0DC9K
DLC Family Code	<a href="#">RRRVZA</a>
Listing Status	Listed
Date Qualified	2020-10-26

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PEU0DC9K
Manufacturer	Back To Earth Energy Inc
Brand	LED IN ACTION
Model Number	BE-SL2-450W-D30
Parent	Yes
Classification	Premium
DLC Family Code	RRRVZA
Input Power Type	AC
Notes	Updated to V5.1 Premium 1/17/22

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

## PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	71956 lm
Reported Efficacy (AC)	160.2 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	74
Reported R9	-28
Reported IES Rf	74
Reported IES Rg	94
Reported IES Rcs,h1	-18
Reported Default Light Output	71956 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	449.2 W
Reported Total Harmonic Distortion	10.2 %
Reported Power Factor	0.972
Reported Default Input Wattage	449.2 W
Voltage Range	100-277 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	71956 lm
Tested Efficacy (AC)	160 lm/W

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	449.2 W

## VERSION HISTORY VIEW DETAILS

2022-01-17	Listed	5.1	Premium
2020-10-26	Listed	5.1	Standard