

INDUSTRIAL LED FLOOD LIGHT

BE-FL27

The FL27 LED flood is built for harsh environments. It's made with anti-corrosion low copper housing and a galvanized bracket. Available with loop-in and loop-out cable entry to minimize wiring.

Ideal for heavy industrial sites and indoor and outdoor applications.

KEY FEATURES:

- Temperature Rating of -30°C up to +50°C
- Built-in 10kV Surge Protection
- Anti-Glare Control
- Pole Mounting Bracket Available
- Copper Housing for Corrosion Resistance
- Polycarbonate Lens
- Standard 5' Pigtail



INVENTRONICS

NICHIA



Dual Cable Entry Options for Daisy Chain Connection

SPECIFICATIONS

Luminous Efficacy	150lm/W
CCT	3000K, 4000K, 5000K (Standard)
CRI	Ra70
Input Voltage	LV: 100-277Vac HV: 277-480Vac
IP Rating	IP66
Lens Degree	55°x125°, 60°, 25°, 26°x60°
LED Driver	Sosen (LV) Inventronics (HV)
Chipset	Nichia
Operating Temp.	-30°C ~ +50°C
Warranty	5 Year Warranty
Certifications	UL, cUL, CE, RoHS

LUMENS	LED WATTAGE
45,000 lm	300W
36,000 lm	240W
30,000 lm	200W
22,500 lm	150W
15,000 lm	100W
7,500 lm	50W

