

HAZARDOUS B-TOP

The B-TOP fixture withstands explosion and fire hazards, as well as flammable gases and vapours. This hazardous location LED light has CID2, CIID1, CIID2, and CIII classification ratings.

Ideal for hazardous environments, petrochemical complexes, painting facilities, offshore platforms, oil and gas complexes, and more.

KEY FEATURES:

- CID2 Group A, B, C, D
- CIID1 Group E, F, G
- CIID2 Group F, G
- CIII
- Crouse-Hinds™ Tophat Adapter
- MeanWell Driver



SPECIFICATIONS

Luminous Efficacy	140lm/W
CCT	3000K, 4000K, 5000K (Standard)
CRI	>70
Input Voltage	LV: 100-277Vac HV: 200-480Vac DC: 12-48Vdc
IP Rating	IP66
Temp. Rating	-40°C ~ +55°C
L70 Lifespan	>50,000 Hours
Top Hat	Crouse-Hinds™
Warranty	5 Year Warranty
Certifications	UL 1598A, cUL, DLC 5.1 Standard
Classifications	CID2 Group A, B, C, D CIID1 Group E, F, G CIID2 Group F, G CIII

LUMENS	LED WATTAGE
28,000 lm	200W
21,000 lm	150W
16,800 lm	120W
14,000 lm	100W
11,200 lm	80W
8,400 lm	60W
7,000 lm	50W
5,600 lm	40W

