

DesignLights Consortium



Model Number	BE-CHB-150W-D120-B-HV-5000K
Classification	Standard
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	150 W
Reported Light Output	23512 lm
Reported CCT	5000 K
Reported CRI (Ra)	73
Product ID	S-I360GA
DLC Family Code	YYYYFHE
Listing Status	Listed
Date Qualified	2022-06-13

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-I360GA
Manufacturer	Back To Earth Energy Inc
Brand	LED IN ACTION
Model Number	BE-CHB-150W-D120-B-HV-5000K
Parent	No
Classification	Standard
DLC Family Code	YYYYFHF
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	23512 lm
Reported Efficacy (AC)	156.75 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	73
Reported R9	-30
Reported IES Rf	74
Reported IES Rg	94
Reported IES Rcs,h1	-18
Reported Default Light Output	23512 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	150 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Default Input Wattage	150 W
Voltage Range	277-480 V

VERSION HISTORY VIEW DETAILS

2022-12-07	Listed	5.1	Standard
2022-12-06	Listed	5.1	Standard
2022-12-05	Listed	5.1	Standard
2022-11-10	Listed	5.1	Standard
2022-06-13	Listed	5.1	Standard