

UNIVERSAL INDUSTRIAL LED LIGHT

600 VAC

600VAC - SL & SL2

The most compact 1000 watt HID equivalent on the market! At 72,000lm or 96,000lm the 600V SuperLux series can deliver ample lumens up to 130' mounting heights. Using only the best quality components proven to last in heavy industrial plants for the past 17 years. Install it anywhere with our universal mounting options including overhead cranes, high bay, flood/area lighting, and outdoor pole/mast lighting.

Ideal for harsh environments found at heavy industrial plants in North America!

KEY FEATURES:

- **600 Vac**
- **72,000 & 96,000 Lumens & 160lm/W**
- Cascading Surge Protection options available for 20kA at luminaire and 50kA at panel
- **6' Standard Pigtail**
- **IP66 & Universal Mounting Options** For Any Industrial Application Inside & Out At Your Facility



450W Model



SPECIFICATIONS

Luminous Efficacy	160lm/W
CCT	5000K, Other Options Available
CRI	>Ra 70
Beam Angle	30°, 60°, 90°, 120° (Standard)
Input Voltage	600Vac
IP Rating	IP66
L70 Lifespan	>100,000 Hours @ 50°C
LED Driver	PowerLand
Chipset	Seoul
Operating Temp.	-40°C ~ +65°C / -40°F ~ +149°F
Warranty	5 Year Warranty
Certifications	DLC, ETL, UL, cUL



600W Model



Scan QR Code Now For 2D/3D Drawings, IES Files, Spec Sheets & More

LUMENS	LED WATTAGE
96,000 lm	600W
72,000 lm	450W

MOUNTING OPTIONS

Mounting Options Shown With 450W Model

<p>HIGH BAY</p>  <p>LOOP HANGING (STANDARD)</p>	<p>AREA/FLOOD LIGHT</p>  <p>BRACKET 16</p>	<p>MAST LIGHT</p>  <p>BRACKET 16 + BRACKET 07 (SLIP FITTER)</p>
--	---	--

Mounting Options Shown With 600W Model

<p>HOOK</p>  <p>HK</p>	<p>90° ALU SHADE</p>  <p>90ALU</p>	<p>VISOR</p>  <p>VISOR</p>
--	--	--

FIXTURE ORDERING MATRIX

Product Name & Wattage	Lens Degree	Input Voltage	CCT	Options
<p>BE-SL2-450W</p> <p>BE-SL(HB17)-600W</p>	<p>D30</p> <p>D60</p> <p>D90</p> <p>D120 (Standard)</p> <p>D120HT (High Temp ROBAX Glass)</p>	<p>SHV 600Vac</p>	<p>5000K</p> <p>Other Options Available</p>	<p>07 Slip Fitter</p> <p>16 Adjustable Bracket</p> <p>HK Hook</p> <p>90ALU 90° Aluminum Shade</p> <p>VISOR Visor</p> <p>SC (Included) Safety Cable</p> <p>SGS (Included) 20kA Surge Suppressor</p> <p>M50 50kA Panel Surge</p>

Example: BE-SL2-450W-D120-SHV-5000K-16-SC-SGS