

UNIVERSAL INDUSTRIAL LED

72,000 LUMEN

The most compact 1000 watt HID equivalent on the market! At only 28 lbs & up to 72,000lm, the SL2 can deliver ample lumens up to 80' mounting heights. Using only the best quality components proven to last in heavy industrial plants for the past 17 years. Install it anywhere with our universal mounting options including overhead cranes, high bay, flood/area lighting, and outdoor pole/mast lighting.

Ideal for harsh environments found at heavy industrial plants in North America!

KEY FEATURES:

- **72,000 Lumens & 160lm/W**
- Industry Leading 20kA Surge Protection (Pre-Installed)
- **Easy Installation:** Only 28 Pounds Including the 347V, 480V Model
- **Easy Access Driver Box with 6' External Pigtail**
- **IP66 & Universal Mounting Options** for Any Industrial Application Inside & Out at Your Facility



Scan QR Code Now For 2D/3D Drawings, IES Files, Spec Sheets & More



SPECIFICATIONS

Luminous Efficacy	160lm/W
CCT	5000K, Other Options Available
CRI	>Ra70
Beam Angle	30°, 60°, 90°, 120° (Standard)
Input Voltage	LV: 100-277 Vac (250 Vdc) HV: 277-480Vac SHV: 600Vac
IP Rating	IP66
L70 Lifespan	100,000 Hours @ 50°C
LED Driver	Inventronics (LV & HV) PowerLand (SHV)
Chipset	Seoul
Operating Temp.	-40°C ~ +65°C / -40°F ~ +149°F
Warranty	5 Year Warranty
Certifications	DLC, ETL, UL, cUL

LUMENS

72,000lm

LED WATTAGE

450W

MOUNTING OPTIONS					
HIGH BAY LIGHT 	AREA/FLOOD LIGHT 	MAST LIGHT 	CRANE LIGHT 		
LOOP HANGING (STANDARD)	BRACKET 24	BRACKET 24 + BRACKET 07 (SLIP FITTER)		BRACKET 24	
FEMALE 3/4" NPT LID 	HOOK 	90°ALU SHADE 	VISOR 		
NPT	HK	90ALU	VISOR		
Fixture Ordering Matrix					
Product Name	Wattage	Lens Degree	Input Voltage	CCT	Options
BE-SL2	450W	D30 D60 D90 D120 (Standard) D120HT (High Temp ROBAX Glass)	LV 100-277Vac HV 277-480Vac SHV 600Vac	5000K Other Options Available	07 Slip Fitter 24 Adjustable Bracket HK Hook 90 ALU 90° Aluminum Shade VISOR Visor NPT Female 3/4" NPT Lid SC (Included) Safety Cable SGS (Included) 20kA Surge Suppressor RM Remote Mount Driver
Example: BE-SL2-450W-D120-A-LV-5000K-24-SC-SGS					