

**UNIVERSAL INDUSTRIAL LED**

**15,000 LM - 48,000 LM**

The most compact 1000 watt HID equivalent on the market! At only 22 pounds and up to 48,000 lumens, the SL3 can deliver ample lumens up to 60' mounting heights. Using only the best quality components proven to last in heavy industrial plants for the past 17 years. Install it anywhere with our universal mounting options including overhead cranes, high bay, flood/area lighting, and outdoor pole/mast lighting.

Ideal for harsh environments found at heavy industrial plants in North America!

**KEY FEATURES:**

- **Up to 48,000 Lumens & 160lm/W**
- Industry Leading **20kA Surge Protection** (Pre-Installed)
- **Easy Installation:** Only 22 lbs Including the 347v, 480v Model
- **Simple Maintenance Driver Box** With Easy Access Terminal Block & 6' Standard Pigtail
- **IP66 & Universal Mounting Options** For Any Industrial Application Inside & Out At Your Facility



**SPECIFICATIONS**

<b>Luminous Efficacy</b>	160lm/W (240W & 300W) 150lm/W (100W-200W)
<b>CCT</b>	5000K, Other Options Available
<b>CRI</b>	>Ra70
<b>Beam Angle</b>	30°, 60°, 90°, 120° (Standard)
<b>Input Voltage</b>	<b>LV:</b> 100-277 Vac (250 Vdc) <b>HV:</b> 277-480Vac <b>SHV:</b> 600Vac (150W-300W)
<b>IP Rating</b>	IP66
<b>L70 Lifespan</b>	100,000 Hours @ 50°C
<b>LED Driver</b>	Sosen (LV) Inventronics (HV), PowerLand (SHV)
<b>Chipset</b>	SEOUL
<b>Operating Temp.</b>	-40°C ~ +65°C / -40°F ~ 149°F
<b>Warranty</b>	5 Year Warranty
<b>Certifications</b>	DLC, ETL, UL, cUL



Scan QR Code Now For 2D/3D Drawings, IES Files, Spec Sheets & More

LUMENS	LED WATTAGE
48,000lm	300W
38,400lm	240W
30,000lm	200W
22,500lm	150W
18,000lm	120W
15,000lm	100W

MOUNTING OPTIONS					
<p><b>HIGH BAY LIGHT</b></p>  <p><b>LOOP HANGING (STANDARD)</b></p>	<p><b>AREA/FLOOD LIGHT</b></p>  <p><b>BRACKET 30</b></p>	<p><b>MAST LIGHT</b></p>  <p><b>BRACKET 07 + BRACKET 30</b></p>	<p><b>CRANE LIGHT</b></p>  <p><b>BRACKET 30</b></p>		
<p><b>FEMALE 3/4" NPT LID</b></p>  <p><b>NPT</b></p>	<p><b>HOOK</b></p>  <p><b>HK</b></p>	<p><b>90° ALU SHADE</b></p>  <p><b>90ALU</b></p>	<p><b>POLYCARBONATE REFLECTOR</b></p>  <p><b>PC</b></p>		
FIXTURE ORDERING MATRIX					
Product Name	Wattage	Lens Degree	Input Voltage	CCT	Options
<b>BE-SL3</b>	<p><b>100W</b></p> <p><b>120W</b></p> <p><b>150W</b></p> <p><b>200W</b></p> <p><b>240W</b></p> <p><b>300W</b></p>	<p><b>D30</b></p> <p><b>D60</b></p> <p><b>D90</b></p> <p><b>D120 (Standard)</b></p> <p><b>D120HT (High Temp ROBAX Glass)</b></p>	<p><b>LV</b> AC 100-277 Vac (250Vdc)</p> <p><b>HV</b> AC 277-480 Vac</p> <p><b>SHV</b> 600Vac (150W-300W)</p>	<p><b>5000K</b></p> <p>Other Options Available</p>	<p><b>07</b> Slip Fitter</p> <p><b>30</b> Adjustable Bracket</p> <p><b>HK</b> Hook</p> <p><b>90 ALU</b> 90° Aluminum Shade</p> <p><b>PC</b> Polycarbonate Reflector</p> <p><b>NPT</b> Female 3/4" NPT Lid</p> <p><b>RM</b> Remote Mount Driver</p> <p><b>SC (Included)</b> Safety Cable</p> <p><b>SGS (Included)</b> 20kA Surge Suppressor</p>
<p><b>Example: BE-SL3-100W-D120-A-LV-5000K-30-SC-SGS</b></p>					