

## HIGH TEMP HAZLOC UP TO 100°C / 212°F

The HH03 fixture withstands extreme temperatures, explosion and fire hazards, as well as flammable gases and vapours. This driverless LED fixture can withstand temperatures up to 100°C with a CID2 classification rating.

Ideal for high heat environments, petrochemical complexes, painting facilities, offshore platforms, oil and gas complexes, and more.

### KEY FEATURES:

- CID2 Group A, B, C, D / CID1 Options Available
- Temp Rating of -40°C to +100°C / -40°F to +212°F
- Built-In 6kV Surge Protection
- Mounting Options
- Driverless Hazardous LED
- 6' Length UL SOOW 105°C 18AWG Cable
- L70 Lifespan of >60,000 Hours



Scan QR Code Now For 2D/3D Drawings, IES Files, Spec Sheets & More



### SPECIFICATIONS

<b>Luminous Efficacy</b>	100 lm/W - COB Chip
<b>CCT</b>	3000K, 5000K (Standard)
<b>CRI</b>	>Ra 70 (5000K), >Ra 80 (3000K)
<b>Beam Angle</b>	>110°
<b>Input Voltage</b>	120V / 230V / 277V
<b>IP Rating</b>	IP67
<b>L70 Lifespan</b>	>60,000 Hours

<b>Operating Temp.</b>	<b>30W-60W:</b> -40°C to +100°C / -40°F to +212°F
	<b>80W:</b> -40°C to +85°C / -40°F to +185°F

<b>Warranty</b>	66°C-85°C - 2 year Warranty 86°C-100°C - 1 Year Warranty
-----------------	---

<b>Certifications</b>	UL, cUL
-----------------------	---------

<b>Classifications</b>	CID2 Group A, B, C, D Ask About Our CID1 Options
------------------------	---

LUMENS	LED WATTAGE
10,000 lm	100W
8,000 lm	80W
6,000 lm	60W
3,000 lm	30W